



Office de la Propriété  
Intellectuelle  
du Canada

Un organisme  
d'Industrie Canada

Canadian  
Intellectual Property  
Office

An agency of  
Industry Canada

CA 2363132 A1 2000/09/08

(21) 2 363 132


(12) DEMANDE DE BREVET CANADIEN  
CANADIAN PATENT APPLICATION

(13) A1

(86) Date de dépôt PCT/PCT Filing Date: 2000/03/01  
(87) Date publication PCT/PCT Publication Date: 2000/09/08  
(85) Entrée phase nationale/National Entry: 2001/08/28  
(86) N° demande PCT/PCT Application No.: GB 2000/000731  
(87) N° publication PCT/PCT Publication No.: 2000/052299  
(30) Priorité/Priority: 1999/03/02 (60/122,530) US

(51) Cl.Int.<sup>7</sup>/Int.Cl.<sup>7</sup> E21B 21/00  
(71) Demandeur/Applicant  
WEATHERFORD/LAMB, INC., US  
(72) Inventeurs/Inventors:  
BOURGOYNE, DARRYL A., US;  
HANNEGAN, DON M., US  
(74) Agent: MARKS & CLERK

(54) Titre : TETE DE CONTROLE ROTATIVE A TUBE PROLONGATEUR INTERNE  
(54) Title: INTERNAL RISER ROTATING CONTROL HEAD



(57) Abrégé/Abstract

A system for providing a barrier between two different fluid densities in a riser while drilling in deep water. An internal housing (20) and a rotating control head (28) are positioned in a first housing (R) when a blowout preventer (GM) is in the sealed

Canada

<http://opic.gc.ca> · Ottawa-Hull K1A 0C9 · <http://cipo.gc.ca>

O P I C



C I P O

(57) Abrégé(suite)/Abstract(continued):

position. When the blowout preventer is in the sealed position about the internal housing, a pipe (P) can be rotated for drilling with the pressure of the fluid in the open borehole at one density (M) and the fluid above the seal at another density (SW). When the blowout preventer seal is in the open position, the threadedly connected bearing assembly and internal housing can be removed relatively quickly from the riser (R). Advantageously, a method for use of the system is also disclosed.